

ΤΣΙΜΠΙΔΕΣ ΗΛΕΚΤΡΟΔΙΩΝ

Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11312	CLAMP EARTH CRABB250 200-250A	8028485132506	€8,33
BS 638.5 / CRABB 250 GROUND CLAMP / Ground clamp with rustproof steel structure. Brass contact and copper plate connection. / Weight215 g / Cable_size25 □ 35 mm ² / DUTY_CYCLE_60perc200 A / DUTY_CYCLE_35perc250 A / Jaws_opening53 mm			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11313	CLAMP EARTH CRABB350 300-400A	8028485131356	€8,57
BS 638.5 / CRABB 350 GROUND CLAMP / Ground clamp with rustproof steel structure. Brass contact and copper plate connection. / Weight320 g / Cable_size50 □ 70 mm ² / DUTY_CYCLE_60perc300 A / DUTY_CYCLE_35perc400 A / Jaws_opening74 mm			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11315	CLAMP EARTH CRABB500 400-500A	8028485131509	€11,99
BS 638.5 / CRABB 500 GROUND CLAMP / Ground clamp with rustproof steel structure. Brass contact and copper plate connection. / Weight560 g / Cable_size70 □ 95 mm ² / DUTY_CYCLE_60perc400 A / DUTY_CYCLE_35perc500 A / Jaws_opening80 mm			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11316	CLAMP EARTH CRABB600 500-600A	8028485131608	€11,99
CRABB 600 GROUND CLAMP / BS 638.5 / Ground clamp with rustproof steel structure. Brass tilting contacts with double copper braid connection. / Weight590 g / Cable_size95 □ 120 mm ² / DUTY_CYCLE_60perc500 A / DUTY_CYCLE_35perc600 A / Jaws_opening80 mm			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11401	FALCON 700 ELECTRODE HOLDER	8028485140150	€31,88
60974-11 class B / FALCON 600 ELECTRODE HOLDER / Tightening of the electrode with lever. Brass body cast and anti-schock coating, clamping device by Allen key, Fixing of electrode in 7 positions. / Cable_size95 mm ² / DUTY_CYCLE_60perc400 A / DUTY_CYCLE_35perc500 A / Max_electrode_diameter8 mm.			



ΤΣΙΜΠΙΔΕΣ ΗΛΕΚΤΡΟΔΙΩΝ



Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11408	FALCON 400 ELECTRODE HOLDER	8028485140808	€17,37
EN 60974-11 class B / FALCON 400 ELECTRODE HOLDER / Tightening of the electrode with lever. Brass body cast and anti-schock coating, / clamping device by Allen key. Fixing of electrode in 7 positions. / Cable_size50 mm ² / DUTY_CYCLE_60perc250 A / DUTY_CYCLE_35perc300 A / Max_electrode_diameter5 mm.			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11409	FALCON 600 ELECTRODE HOLDER	8028485140907	€21,99
60974-11 class B / FALCON 600 ELECTRODE HOLDER / Tightening of the electrode with lever. Brass body cast and anti-schock coating, clamping device by Allen key. Fixing of electrode in 7 positions. / Cable_size70 mm ² / DUTY_CYCLE_60perc300 A / DUTY_CYCLE_35perc400 A / Max_electrode_diameter6,3 mm.			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11411	SUPER 300 ELECTRODE HOLDER	8028485141102	€13,19
SUPER 300 ELECTRODE HOLDER / EN 60974-11 class B / Tightening of the electrode with lever. Brass body cast and anti-schock coating, clamping device by Allen key. Fixing of electrode in 3 positions. / Cable_size25 mm ² / DUTY_CYCLE_60perc150 A / DUTY_CYCLE_35perc200 A / Max_electrode_diameter3,2 mm.			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11413	SUPER 500 ELECTRODE HOLDER	8028485141300	€18,12
SUPER 500 ELECTRODE HOLDER / EN 60974-11 class B / Tightening of the electrode with lever. Brass body cast and anti-schock coating, clamping device by Allen key. Fixing of electrode in 3 positions. / Cable_size50 mm ² / DUTY_CYCLE_60perc250 A / DUTY_CYCLE_35perc300 A / Max_electrode_diameter5 mm.			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11414	SUPER 600 ELECTRODE HOLDER	8028485141409	€20,98
SUPER 600 ELECTRODE HOLDER / EN 60974-11 class B / Tightening of the electrode with lever. Brass body cast and anti-schock coating, clamping device by Allen key. Fixing of electrode in 3 positions. / Cable_size70 mm ² / DUTY_CYCLE_60perc300 A / DUTY_CYCLE_35perc400 A / Max_electrode_diameter6,3 mm.			

ΤΣΙΜΠΙΔΕΣ ΗΛΕΚΤΡΟΔΙΩΝ

Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11416SL	MAX 200 ELECTRODE HOLDER	8028485141607	€9,00
EN 60974-11 class B / Tightening of the electrode with lever. Brass body cast and anti-schock coating, clamping device by Allen key. Fixing of electrode in 7 positions. / Cable_size16 □ 25 mm ² / DUTY_CYCLE_60perc150 A / DUTY_CYCLE_35perc200 A / Max_electrode_diameter3,2 mm.			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACF11808S	CHIPPING HAMMER	8028485180811	€4,21
CHIPPING HAMMER WITH STEEL HANDLE - SMALL / Steel chipping hammer with tempered tip and iron handle. / Length315 mm / Weight250 g			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACPIN000059	HOLDER ELECTRODE 300 URANIA	8028485030611	€20,57
EN 60974-11 class B / URANIA 3 ELECTRODE HOLDER / flame resistant and heat-proof. Cable clamping by recessed hex-head dowels. Insulated / compression spring. Die-cast brass lever insulated with thermosetting Material. Fixing electrode in 5 positions. / Weight325 g / Cable_size16 □ 25 mm ² / DUTY_CYCLE_60perc150 A / DUTY_CYCLE_35perc200 A / Max_electrode_diameter2 3,2 mm			




Κωδικός	Περιγραφή	Barcode	Τιμή
SACPIN000070	HOLDER ELECTRODE 400 URANIA	8028485030628	€26,16
EN 60974-11 class B / URANIA 3 ELECTRODE HOLDER / Die-cast brass body and insulating coatings in thermosetting materials, flame resistant and heat-proof. Cable clamping by recessed hex-head dowels. Insulated compression spring. Die-cast brass lever insulated with thermosetting Material. Fixing electrode in 5 positions. Weight425 g. Cable_size25 □ 35 mm ² / DUTY_CYCLE_60perc200 A / DUTY_CYCLE_35perc250 A / Max_electrode_diameter2,5 4 mm.			




Κωδικός	Περιγραφή	Barcode	Τιμή
SACPIN000081	HOLDER ELECTRODE 500 URANIA	8028485030635	€28,90
EN 60974-11 class B / URANIA 5 ELECTRODE HOLDER / Die-cast brass body and insulating coatings in thermosetting materials, / flame resistant and heat-proof. Cable clamping by recessed hex-head dowels. Insulated / compression spring. Die-cast brass lever insulated with thermosetting Material. Fixing electrode in 3 positions. / Weight495 g Cable_size35 □ 50 mm ² / DUTY_CYCLE_60perc250 A / DUTY_CYCLE_35perc300 A / Max_electrode_diameter3,2 5 mm.			




ΤΣΙΜΠΙΔΕΣ ΗΛΕΚΤΡΟΔΙΩΝ



Κωδικός	Περιγραφή	Barcode	Τιμή
SACPIN000101	HOLDER ELECTRODE 600 URANIA	8028485030673	€30,10
EN 60974-11 class B URANIA 6 ELECTRODE HOLDER Electrode holder that allows the electrode clamping in a single position by rotation of the handle. Weight690 g / Weight690 g / Weight690 g / DUTY_CYCLE_60perc300 A DUTY_CYCLE_35perc400 A / Max_electrode_diameter4 6,3 mm			




Κωδικός	Περιγραφή	Barcode	Τιμή
SACPIN000097	HOLDER ELECTRODE 600 SUPERIOR	5291811020348	€42,64
SUPERIOR 6 ELECTRODE HOLDER / EN 60974-11 class B / Electrode holder that allows the electrode clamping in a single position by rotation of the handle. Weight690 g / Cable_size50 70 mm² / DUTY_CYCLE_60perc300 A DUTY_CYCLE_35perc400 A / Max_electrode_diameter4 6,3 mm.			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACMRS000054	CLAMP EARTH DELTA 6 ROTARY	8028485134708	€21,01
DELTA 6 GROUND CLAMP regulations BS 638.5 / Ground clamp with screw-fastening system and tilting contact; specific for fixed high amp work stations. Weight840 g Cable_size70 95 mm² / DUTY_CYCLE_60perc500 A / DUTY_CYCLE_35perc600 A / Jaws_opening50 mm			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACMRS000060	OK 4 GROUND CLAMP 250-300A	8028485024184	€10,55
OK 4 GROUND CLAMP / Ground clamp with pressed steel structure, steel contacts and copper shunt. Cable is screw-fastened directly onto the contact zone / Weight260 g / Cable_size50 70 mm² / DUTY_CYCLE_60perc400 A DUTY_CYCLE_35perc500 A / Jaws_opening65 mm			



Κωδικός	Περιγραφή	Barcode	Τιμή
SACMRS000057	OK 2 GROUND CLAMP 250-300A	8028485024177	€9,89
OK 2 GROUND CLAMP / Ground clamp with pressed steel structure, steel contacts and copper shunt. Cable is screw-fastened directly onto the contact zone. / Weight210 g / Cable_size35 50 mm² / DUTY_CYCLE_60perc250 A DUTY_CYCLE_35perc300 A / Jaws_opening52 mm			

ΤΣΙΜΠΙΔΕΣ ΗΛΕΚΤΡΟΔΙΩΝ

Κωδικός	Περιγραφή	Barcode	Τιμή
SACMRS000068	OK 1 GROUND CLAMP 200-250A	8028485024207	€4,17
OK 1 GROUND CLAMP / Ground clamp with pressed steel structure, steel contacts and copper shunt. Cable is screw-fastened directly onto the contact zone. Weight205 g / Cable_size25 35 mm ² / DUTY_CYCLE_60perc200 A / DUTY_CYCLE_35perc250 A / Jaws_opening45 mm			



Κωδικός	Περιγραφή	Barcode	Τιμή
CABLE16	CABLE WELDING 16mm	5291811167579	€3,92
RUBBER CABLE H01N2-D 16MM ² - 100MT / H01N2-D HAR / Specific cable for welding, in compliance with standards and the European low voltage directive. / Maximum operating temperature: 90°C on conductor. / Insulating material: Type EM 5 rubber. Sheath colour: black. Marking: SARPREEN H01N2-D HAR. Weightkg 0,20 / Cable_size16 mm ² / DUTY_CYCLE_60perc160 A / DUTY_CYCLE_35perc235 A / DUTY_CYCLE_100perc125 A / RESISTANCE1,210 Ohm/km / Maximun_temperature90°			

Κωδικός	Περιγραφή	Barcode	Τιμή
CABLE25	CABLE WELDING 25mm	5291811007578	€6,07
RUBBER CABLE H01N2-D 25MM ² - 100MT / H01N2-D HAR / Specific cable for welding, in compliance with standards and the European low voltage directive. / Maximum operating temperature: 90°C on conductor. / Insulating material: Type EM 5 rubber. Sheath colour: black. Marking: SARPREEN H01N2-D HAR. / Weightkg 0,29 / Cable_size25 mm ² / DUTY_CYCLE_60perc210 A / DUTY_CYCLE_35perc320 A / DUTY_CYCLE_100perc170 A / RESISTANCE0,780 Ohm/km / Maximun_temperature90°.			

Κωδικός	Περιγραφή	Barcode	Τιμή
CABLE35	CABLE WELDING 35mm	8028485003271	€9,34
RUBBER CABLE H01N2-D 35MM ² - 100MT / H01N2-D HAR / Specific cable for welding, in compliance with standards and the European low voltage directive. / Maximum operating temperature: 90°C on conductor. / Insulating material: Type EM 5 rubber. Sheath colour: black. Marking: SARPREEN H01N2-D HAR. / Weightkg 0,41 / Cable_size35 mm ² / DUTY_CYCLE_60perc260 A / DUTY_CYCLE_35perc400 A / DUTY_CYCLE_100perc215 A / RESISTANCE0,554 Ohm/km / Maximun_temperature90°.			

Κωδικός	Περιγραφή	Barcode	Τιμή
CABLE50	CABLE 50mm	-	€9,50
RUBBER CABLE H01N2-D 50MM ² - 100MT / H01N2-D HAR / Specific cable for welding, in compliance with standards and the European low voltage directive. / Maximum operating temperature: 90°C on conductor. / Insulating material: Type EM 5 rubber. Sheath colour: black. Marking: SARPREEN H01N2-D HAR. / Weightkg 0,56 / Cable_size50 mm ² / DUTY_CYCLE_60perc345 A / DUTY_CYCLE_35perc510 A / DUTY_CYCLE_100perc275 A / RESISTANCE0,386 Ohm/km / Maximun_temperature90°			