

SIPHONED GULLY WITH LATERAL EXIT



INDEX

1. Code Registry
2. Use
3. Technical Specification

1. CODE REGISTRY

Code	Description	Dimensions (mm)	Weight	Pkg. / Pallet
TER07-1340	Siphoned Gully with lateral Exit (PP grating and frame)	105 x 105	0,090 kg/pc.	60 pcs / 720 pcs
TER07-1340I	Siphoned Gully with lateral Exit (AISI 304 Stainless steel grating and PP frame)	105 x 105	0,210 kg/pc.	30 pcs / 900 pcs

MATERIAL

Made of PP (polypropylene). The grating is AISI 304 stainless steel.

2. USE

Used for the collection and drainage of stormwater or wash terraces, showers and areas where you need to collect wastewater.

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.D.TER07.1340x	Supply and installation of siphoned gully with AISI 304 Stainless steel BA grating, resistant to weathering and chemical elements, packed in blister. The bottom outlet is provided with a gasket and it can be easily coupled to the cover. The shape and the adjustable grating allow a fast installation for a perfect siphoning system, very simple to inspect. Both available with PP or AISI 304 Stainless steel frame and grating. Measures are 105 x 105 mm; the internal outlet dimensions are 45 mm the external one is 50 mm. Made of PP (polypropylene). The grating is AISI 304 stainless steel. Used for the collection and drainage of stormwater or wash terraces, showers and areas where you need to collect wastewater.		
Dak.D.TER07.1340	PP grating and frame.....	pc.	-
Dak.D.TER07.1340I	AISI 304 Stainless steel grating and PP frame.....	pc.	-