

decofill Instant Filler for interior and exterior use

decofill Instant Spachtel fuer innen und aussen

Ready for use, weather resistant synthetic filler compound for use indoors and outdoors.

Instructions for use: *decofill instant Filler* is ideally suited for improving, smoothing and coating uneven, rough ceilings, walls and facades as well as for reliable, widespread filling and smoothing of prefabricated concrete elements, lime, cement and gypsum based plasters. Can also be used on all mineral surfaces (concrete, air-entrained concrete, clay tiles, etc.) as well as emulsion paints and gypsum boards.
Not suitable for filling works on wood, metal, glass and plastic.

Technical specifications:

Components:	Styrene-acrylate emulsion, fillers and additives
Density:	1.80 g/cm ³
pH-value:	8-9
Usage:	approx. 1.7 kg/m ² for a 1 mm coat thickness
GISBAU product code:	M-DF02

Surface preparation: Prime highly absorbent, sanding and chalking surfaces with *decotric Deeply Penetrating Primer – Solvent Free* or *LH Universal*. The surface must be dry, firm and free of dust and grease. Remove old, peeling wallpapers and distemper paints using *decotric Wallpaper Remover*. Make good cracks and holes using *decotric Interior* or *decomur Super Bonding Filler* or outdoors with *decomur Exterior Façade Filler* or *decofill Exterior*.

Application: Apply *decofill instant Filler* onto the surface up to a thickness of max. 5 mm using a smoothing trowel. Unevenness can be smoothed or felted over when moist. Do not apply subsequent coats of paint or adhesive until the filled area has completely dried.

It is not necessary to prime the surface for subsequent wallpapering and painting works.

Do not use if the surface and/or room temperature is less than +5° Celsius. Clean tools in water immediately after use.

Storage: Store in a cool but frost-free place! Keep the containers tightly sealed!

Available sizes:

400 g PE tube	033306001
1 kg plastic tin	033302001
4 kg plastic tub	033303001