TECHNICAL SPECIFICATION



EVO® Goggle Single Lens

Liquid & Dust N Rated / AGM020-623-000



DESCRIPTION

Engineered to offer outstanding performance, compatibility and comfort, with the option to fit RX inserts enabling safe use of prescription lenses. Standard single lens goggle for general protection, with EVA foam surround for enhanced comfort and improved fit.

OPTIONS

Liquid & Dust N Rated (AGM020-623-000)

SAFETY STANDARDS

EN 166 • EN 170















SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number

2C



Manufacturer's Trademark

JSP Dagger



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.



Protection from Liquid Droplets



Resistance to Molten Metals and Hot Solids (optional)

RX Insert Optional



LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2



Optical Class (1 - Class 1 - High quality for regular use. 2 -Class 2 - Medium quality for occasional use. 3 - Class 3 -Low quality for exceptional use)



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional

Т



Protection from Large Dust Particles (up to 40 um grain size)

4



Resistance to fogging (optional)

Ν



Product Weight

100g

FEATURES



Compatibility

Low profile design means the EVO® Goggle can be worn with an industrial safety helmet or bumpcap.



Comfort

Foam surround on the goggle housing for comfort and to ensure a good fit across a wide range of facial profiles.



RX Inserts

RX inserts are available for the EVO® Goggle range, for combined prescription and safety eyewear. Inserts can be taken to an optician for glazing with corrective lenses.

RANGE



DOWNLOADS



Image Pack (ZIP)



doc-evo-idv-goggle.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





