

TECHNICAL SPECIFICATION



Pioneer™ 2m Adjustable Work Positioning Lanyard

Pioneer™ 2m Adjustable Work Positioning Lanyard / FAR0208



DESCRIPTION

Adjustable length up to 2m, made from 33mm wide polyester webbing with a manual ring type adjuster made of forged alloy steel for ease of adjustment.

OPTIONS

Pioneer™ 2m Adjustable Work Positioning Lanyard (FAR0208)

SAFETY STANDARDS

EN 358



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 28 Jul 2022 / Copyright 2018 - 2022, JSP Limited. All Rights Reserved.



SPECIFICATIONS

Length
2m Max.

Rope Ends
X

Adjustment Device
Manual Ring Type Adjuster Of Forged Alloy Steel

Delivered With
2 Captive Eye Quarter Turn Aluminium Connectors.
Gate Opening 22mm. Conforms To EN362 Class T

Material
33mm Polyester Webbing

Protective Rope Sleeve
No



Product Weight
587g

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0208-far0208e.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 28 Jul 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.

