

TECHNICAL SPECIFICATION



Spartan™ 2m Twin Fall Arrest Lanyard

Spartan™ 2m Twin Fall Arrest Lanyard / FAR0307



DESCRIPTION

Spartan™ fall arrest lanyards are manufactured in 33mm flat webbing with steel connectors. Complete with karabiner and 2 scaffold hooks.

OPTIONS

Spartan™ 2m Twin Fall Arrest Lanyard (FAR0307)

SAFETY STANDARDS

EN 355



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 28 Jul 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Fall Indicator
Yes

Length
2m

Material
30mm Polyester Webbing With Textile Loops On
Both Ends

Shock Absorber
External

Sharp Edge
No

Rope Ends
X

Protective Rope Sleeve
No



Product Weight
1700g

Delivered With
1 Screw Gate Connector In Alloy Steel. Gate
Opening 18mm. Conforms to EN362 Class B & M. 2
Alloy Steel Scaffold Hooks. Gate Opening 50mm.
Conforms to EN362 Class T.

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0307-far0318.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 28 Jul 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.

