

Spartan[™] 2m Adjustable Work Positioning Lanyard

Spartan[™] 2m Adjustable Work Positioning Lanyard / FAR0308



DESCRIPTION

Work positioning and restraint lanyard, adjustable up to 2m, made from 14mm polyamide 3-strand rope (complying with ISO 1140).

OPTIONS

Spartan[™] 2m Adjustable Work Positioning Lanyard (FAR0308)

SAFETY STANDARDS

EN 358



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Length 2m Max.

Rope Ends

Stitched and Covered With Polyethylene Protective Sleeve. Abrasion Resistant Thimbles Provided Within Loops

Adjustment Device

Manual Ring Type Adjuster Of Forged Alloy Steel

Delivered With

2 Screw Gate Connectors In Alloy Steel. Gate Opening 18mm. Conforms To EN362 Class B & M.

DOWNLOADS

- Image Pack (ZIP)
- doc-far0308-far0312.pdf (PDF)

Material

14mm Polyamide 3 Strand Twisted Rope (Complying To ISO 1140). Black and Red Tracer In The Rope To Indicate Degradation of Material.

Protective Rope Sleeve No



Product Weight 770g



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.