

## 2m Adjustable Work Positioning Lanyard with Rope Grab

2m Adjustable Work Positioning Lanyard with Rope Grab / FAR0420



### DESCRIPTION

2m work positioning lanyard with non-openable aluminium rope grab with 2 screw gate connectors in alloy steel. Rope ends stitched and covered with polyethylene protective sleeve.

### OPTIONS

**2m Adjustable Work Positioning Lanyard with Rope Grab (FAR0420)**

### SAFETY STANDARDS

EN 358



## SPECIFICATIONS

Length  
2m Max.

Rope Ends  
Stitched and Covered With Polyethylene Protective Sleeve. Abrasion Resistant Thimbles Provided Within Loops

Adjustment Device  
Non Openable Rope Grab, Aluminium

Delivered With  
2 Screwgate Connectors In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M

Material  
12mm High Quality Kernmantle Rope

Protective Rope Sleeve  
60cm



Product Weight  
1900g

## DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0420-far0421.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 28 Jul 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.

