TECHNICAL SPECIFICATION



EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet Vented

White / AKF170-000-100



DESCRIPTION

The EVO®5 Olympus® safety helmet combines a super strong ABS shell designed for superior all day protection with the comfort benefits of the Evolution® 3D-Adjustment $^{\text{TM}}$ harness system.

EVO®5 Olympus® Industrial safety helmet passes all relevant industrial international standards.

OPTIONS

White (AKF170-000-100)

Blue (AKF170-000-500)

Orange (AKF170-000-800)

Green (AKF170-000-300)

Grey (AKF170-000-400)

Yellow (AKF170-000-200)

Red (AKF170-000-600)

SAFETY STANDARDS

EN 397 • ANSI/ISEA Z89.1 • CSA Z94.1







Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







SPECIFICATIONS



Peak Mid



Lateral Deformation Yes



Maximum Temperature





ABS Shell Yes



Textile Harness



Wheel Ratchet





Ventilation Yes



Integrated Eyewear Optional



BSI Kitemark

Yes



Optional 4 point chinstrap (EN397 Compliant)





Product Weight

372g



Impact Resistance 50 Joules



Molten Metal Yes



Minimum Temperature



-40°C



Recyclable Shell



Depth Adjustment 3D Harness



Universal Accessories Slot

Yes



Reflective Option

Optional



ID card holder





Optional 2 point chinstrap (EN397 & EN 812 compliant)

Optional



JSPCheck

Yes

FEATURES



Tough ABS Shell

The EVO®5 safety helmet features an extremely robust ABS shell designed for superior protection. It features a distinctive five stripe design and the JSP Shield.



Textile Harness

A 6 point terylene cradle harness system & Egyptian cotton Chamlon™ sweatband offers unrivalled comfort.



CR2 Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. The Revolution® wheel ratchet makes it simple to tighten to the perfect fit.



3D Adjustment

The textile harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.



Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors and ear defenders. EVOSpec® Integrated eyewear is also available.



Ventilation Option

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.





LOGO RANGE

✓ Front

✓ Back

✓ Sides



DOWNLOADS

Image Pack (ZIP)

doc-invincible-evo5.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

 $Tel: +44 \ (0) \\ 1993 \ 826050 \ / \ Fax: +44 \ (0) \\ 1993 \ 824411 \ / \ Email: \\ sales@jspsafety.com \ / \ Web: \\ www.jspsafety.com \ / \ Web: \\ www.js$





