



**SAFETY SYSTEM®**  
YOUR PROTECTOR

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 - Fax +39 075.8048686


VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575  
Fax +39 02.90394441

**TECHNICAL SHEET**


**export@sirsafety.com**  
**www.sirsafety.com**

Quality Management  
System Certificate  
UNI EN ISO 9001:2015

<b>Name: ELECTRO GLOVE CLASS 0</b>	<b>Code: MA1814E0</b>	<b>MA18 SPECIAL PROTECTION GLOVES</b>
------------------------------------	-----------------------	---------------------------------------

<p><b>Description</b> Dielectric glove Class 0 Length: 36 cm Thickness: mm 1,0 (tolerance +0,6) in Natural Latex Insulation: 5.000 V Proof test voltage: 5 kV Withstand voltage: 1,0 kV</p> <p>Supplied in a special polyethylene sealed case.</p> <p>The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.</p>	
---	---

Category <b>III</b>	Colours <b>YELLOW</b>	Available Sizes <b>8 - 11</b>
------------------------	--------------------------	----------------------------------

Quantity/Carton          <b>1</b>	<p>EC Standards <b>IEC 60903</b></p> <p> Acid, Oil, Ozone:R Resistant to very low temperatures:C</p>	<p>Important Information</p> <p>Protection against contact with voltage-carrying parts under voltage.</p> <p>Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it. We recommend six-monthly voltage test.</p> <p>Store the gloves in their original sealed case, in a dry place far from the light, at a temperature between <math>5^{\circ}\text{C}</math> » <math>30^{\circ}\text{C}</math>.</p> <p>If gloves become soiled with sticky substances or dyes, they shall be rubbed with suitable solvents, without brushes or abrasive paper. Do not use naphtha, gasoline, liquid paraffin, toluene, xylene, etc. Then wash with water at a temperature below <math>60^{\circ}\text{C}</math> and soap and dry thoroughly.</p> <p>Storage and cleaning Data retrieval failed for the subreport,</p>
Dexterity		