



BEESWIFT[®]
FOCUSED ON SAFETY

Product Code:


NG18


Selling UOM:

Each

Pack Size:

1

 Cat 3 - High Risk

 Chemical Hazards

 Mechanical Handling

SPECIFICATION SHEET

NITRILE GREEN 18"



- Unsupported nitrile glove.
- Overall Length 45cm
- A high level of resistance to abrasion, solvents and animal fats.
- Pebble finish to palm
- Silicon and wax free
- EN ISO 374-1: 2016: Type B
Chemical - Breakthrough Time
Methanol (A) - More than 60 Mins (Level 3)
Toluene (F) - More than 10 Mins (Level 1)
n-Heptane (J) - More than 480 Mins (Level 6)
Sulphuric Acid 96% (L) - More than 240 Mins (Level 5)
Sodium Hydroxide 40% (K) - More than 480 Mins (Level 6)
- EN388: 2016
• Level 4 - Abrasion
• Level X - Cut Resistance
• Level 0 - Tear Resistance
• Level 2 - Puncture
• Level X - ISO 13997 Blade Cut
- EN ISO 374-5:2016
Protection Against Bacteria and Fungi - Pass
Protection Against Viruses - Not Tested



Packaging Waste	Type	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	880.00	494.00	408.00	190.00
Plastic	Inner	10	6.71			
Plastic	Inner	50	7.11			
Paper	Inner	50	3.25			
Carton Weight:		9.88kg				