

ΔΙΠΛΗ ΠΡΟΣΤΑΣΙΑ ΣΕ ΕΝΑ ΜΟΝΟ ΣΥΣΤΗΜΑ



Pantera Air System, το φορητό σύστημα που προστατεύει ταυτόχρονα τα μάτια και την αναπνευστική οδό



ΕΦΑΡΜΟΓΕΣ



MIG (GMAW)



TIG (GTAW)



SMAW



OXYGAS



GRINDING



1/1/1/1

OPTICAL CLASS



100 x 60

VIEWING AREA



114 x 133

FILTER DIMENSIONS



4

SENSORS



DIN 4

LIGHT STATE



< 0,08 ms

SWITCHING TIME



E

POWER SUPPLY



0,1 ÷ 0,9 s

DELAY



LOW BATTERY INDICATOR



DIN 15

UV/IR PROTECTION



DIGITAL

CONTROLS



PAPR



TO FROM
DIN
4 / 9 ÷ 13

SHADE RANGE



CR2450 Li

REPLACEABLE BATTERIES



SENSITIVITY



g
800

NET WEIGHT





Filter type	TH3 P R SL
Filter efficiency level	99,8% 0,3 µm
Airflow level	1 st speed: 170 l/min 2 nd speed: 200 l/min 3 rd speed: 230 l/min
Noise level	Max 75 dB
Belt size	900 ÷ 1300 mm
Blower unit size	240 x 165 x 70 mm
Blower unit weight	1,1 Kg
Battery model	Rechargeable Li-ION 4400 mAh
Battery life	1 st speed > 8 h 2 nd speed > 6 h 3 rd speed > 4 h
Battery charge time	3,5 h
Number of battery recharges	500
Information on the digital display	Air flow rate and data Battery level Filter status
Usage temperatures	-5°C +55°C
Storage temperatures	-10°C +55°C

