

PRODUCT SPECIFICATION

ARTICLE
J2023 S3 BLACK CEMENT

Article J2023 S3 CEMENT Weight 1,160 Kg SIZE 42 Color BLACK

Description of the article: safety shoe, low model, printed water resistant leather, lining CAMBRELLA, double density outsole in Pu, steel toecap and steel midsole.

SECURITY CATEGORY
S3SRC

	TECHNICAL DETAILS	IM A
ype of PPE	Safety shoe for professional use in compliance with low EN ISO	
Main features	Black low model of safety shoe in printed leather, Double layer sole in soft latex, antistatic, anti bacterial with SANITIZED treatment, lined in breathable and high scratch resistant fabric. Mesh Cambrella lining, good breathable. Green stitching. Black-green laces and iron eyelets. Steel toecap, resistant up to 200 J. Steel midsole,. Test results: resistance improved more than 20% to nail's Perforation (diameter 4,5mm) comparable to a strength of 1360 N instead of 1100 N requested by EN 12568. Double density outsole, antistatic, anti spilt, resistant to oil spilt and, injected on the upper.	
	injected on the upper. - First injection in PU of grey color. Shock absorber main features. - Land outsole very resistant in PU	
Security category	S3	Serca,
Law	CE UNI EN ISO20345:2011 – SAFETY SHOES	
Main features	UNI EN ISO 20345:2011 – Safety shoe with toe capacity resistance up to 200 J ENV 13287:2000 – Anti slip resistance Directive 1907/2006/CE – Determination of dangerous substances for leather and fabric elements. Directive 1907/2006/CE – Determination of the level of nickel for the metal parts in contact with the foot. This safety shoe S3SRC is in compliance with the law EN 20345:2011	
Manufactured by	CALZATURIFICIO 5BI-ITALY	
	MADE IN ITALY	