

TECHNICAL DATA SHEET ANTI-SLIP TAPE – ABRASIVE

Protection even when exposed to heavy traffic, water or grease.

4. Use indoors or outdoors.

5. Self-adhesive backing sticks to painted wood, metal, and sealed concrete.

6. Easy to tear by hand.

MEASURES: mm.25x18 mt. or 50x18 mt.



Technical specification

Material Sanded PVC film

Material of sand Corundum c

Mesh of sand: 80 Mesh

Glue solvent based rubber glue

Foil thickness: 150 Mic

Total thickness: 800 Mic

Release film:

White PE coated Silicone Release Paper

Release film thickness:

120 Mic

PROPERTIES	UNIT	VALUE	TEST METHOD
First Adhesive (# 11 Steel Ball)	CM	≥ 10	PSTC-6
Persistent strength	H.25 mm.	≥24	PSTC-7
180° C Peeling strength	N/25mm	4.5	PSTC-1
Tensile strength	N/25mm	50	PSTC-31
Elongation	%	180	PSTC-31
Tear resistance	N	50	ASTM D-732
Water resistant	Month	≥10	
UV Resistant	/	Yes	
Fire Resistant	Class	V-0	UL94
Moisture Resistant	Month	≥8	
Application Temperature	°C	0 ~ +40	
Temperature Resistance	°C	-20 ~ +50	
Shelf Life	Month	≥ 24	At approx. +20°C and 50% humidity

SOIANO, 25105126

COMBY-ITALIA S.r.l. Socio Unico

Sede Legale, Amm. Op. : Via delle Pozzette, 13/A
(Z.I. Levrini) - 25080 SOIANO DEL LAGO (BS)

P.IVA 01897710982

Tel. 0365 671006 www.combyitalia.it

Sede Legale: Via Roma, 28 - 25080 PADENGHE (Brescia)

Sede Amministrativa ed Operativa: Via delle Pozzette, 13/A (Z.I. Levrini) - 25080 SOIANO DEL LAGO (Brescia) - ITALIA

Telefono: 0365.67.10.06 r.a. • Fax 0365.50.35.01 • P. IVA: 01897710982 • Cap. Soc. € 90.000 i.v.

Reg. Imp. BS n. 515042/1996 R.E.A. 0368620 • M. Export BS 062403 • E-mail: info@combyitalia.it • Web: <http://www.combyitalia.it>