

# ASCD 18-200 W4 AS cordless impact wrench

## Cordless impact wrench/driver

Up to max. 210 Nm with brushless motor and 6-stage torque setting. For universal screwdriving applications including self-drilling screwdriving.

Product number: 7 115 11 61 00 0

## Details

- For extreme precision work: The ASCD 18-200 W4 AS with electronic torque setting (6 levels) prevents screw heads from shearing off.
- Brushless motor with 30% higher efficiency and long service life.
- 1/4" hexagon socket tool mounting for holding bits and socket wrench inserts.
- 10% more torque in reverse running to loosen screws which are extremely tight.
- Robust solid metal impact gear.
- Contact guard on gearbox head.
- Compact design.
- 700 screw connections (M18) with one battery charge (ProCORE 4 Ah).
- Bit and belt holder on the side for ergonomic and flexible handling.
- Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

## Price includes

- 1 belt clip
- 1 tool case (L-Boxx 136)
- 1 magnetic bit storage

## Technical data

### TECHNICAL DATA

| | |
|---|---|
| Battery voltage | 18 V |

### VIBRATION AND SOUND EMISSION VALUES

| | |
|---|---|
| Sound pressure level LpA<br>Uncertainty of measured value KpA | 96,1 dB<br>3 dB |

| | |
|---|---|
| Battery compatibility | Li-ion / ProCORE Li-ion |
| Battery interface | 18 V AMPShare |
| Motor | brushless |
| Speed, no load | 0 - 1 500 rpm |
| Impacts | 0 - 3 000 rpm |
| Max. torque | 210 Nm |
| Torque levels | 6 |
| Tool Holder | 1/4 in hexagon socket |
| Wood screw Ø | 8 x 200 mm |
| Weight without storage battery | 1.20 kg |

| | |
|---|---|
| Sound power level LWA<br>Uncertainty of measured value KWA | 104,1 dB<br>3 dB |
| Sound peak value LpCpeak<br>Uncertainty of measured value KpCpeak | 118,1 dB<br>3 dB |
| Vibration value 1 αhv 3-way<br>Uncertainty of measured value Kα | αh 13,4 m/s²<br>1,5 m/s² |

## Application examples

**Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus.** | Compatible with AMPShare/Bosch Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.





