

Cordless impact drill/driver ASB 18 Q AS (in box)

2-speed cordless combi drill

With brushless motor and QuickIN interface. Perfectly suited to drilling up to 13 mm in metal, stone and masonry.

Product number: 9 910 00 01 55 7

Details

- 2-speed solid metal gearbox and switchable striking mechanism for optimum drilling in metal, stone and masonry.
- Enjoy the greatest versatility with the FEIN QuickIN system. Work at speed in metal and timber with just one tool.
- QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces.
- Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- Mechanical torque setting.
- Compact design.
- The AMPShare interface makes almost 50% more screw connections (approx. 1300 screw connections, diameter of 5 x 40 mm in timber) possible per battery charge with the same level of FEIN quality. (ProCORE 4 Ah).
- Bit and belt holder on the side for ergonomic and flexible handling.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. “Electronic Cell Protection” (ECP) protects the battery from overload, overheating and total discharge.

Price includes

- 1 QuickIN drill chuck (120 Nm)
- 1 belt clip
- 1 magnetic bit storage

Product feature

- Removable drill chuck
- Switchable impact mechanism
- QuickIN accessory interface

Technical data

TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Motor	brushless
Gearbox	2-speed
Accessory interface	QuickIN
Speed, no load	450 / 2,000 rpm
Impacts	7,360 / 32,000 rpm
Max. torque (hard/soft)	60 / 38 Nm
Torque levels	22 + 1
Drill chuck clamping width	1.5 - 13 mm
Fastening	8 x 300 mm
Drill Ø steel twist drill	13 mm
Capacity in wood Ø	50 mm
Capacity in stone Ø	13 mm
Tapping	M 10
Weight without storage battery	1.19 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	92,9 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	100,9 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	110,0 dB 3 dB
Vibration value 1 αhv 3-way Uncertainty of measured value Kα	ah,D 1,4 m/s² 1,5 m/s²
Vibration value 2 αhv 3-way Uncertainty of measured value Kα	ah 0,6 m/s² 1,5 m/s²

Application examples



Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.